



Product introduction

Micronized Polyamide Wax

Chemical composition

Polyamide

Features and advantages

1. Excellent anti-sag performance;
2. Excellent anti-precipitation performance;
3. Lighter color.
4. High thickening efficiency.

Recommended use

1. Applicable to various solvent-based systems such as anti-corrosion coatings;
2. Applicable to various non-aqueous systems such as solvent-free.
3. Suitable for high-solid-content coatings such as UV coatings

Recommended dosage

0.5-2.0% of total formula

Technical data

Melting point (°C):	130
Average particle size (D50):	3-5
Exterior:	white powder

Processing guidance

1. The product can be added at all stages;
2. Avoid high temperature during the production process;
3. Maintain a temperature of 50 °C -70 °C in the coating system for activation for at least 30-40 minutes; It can also be activated by dispersing equipment such as sand mills.

Storage and transportation

1. Cool, dry and ventilated, below 60°C, and not close to fire;
2. Shelf life in airtight containers is two years.

Package

20kg paper bag.

We provide these data and technical advice with our existing knowledge. However, because of the different application environment, please users according to the test application, we can not guarantee all the circumstances.

JIANGSU TIANWEN NEW MATERIAL TECHNOLOGY CO.,LTD.
Xinbei District Changzhou Jiangsu
Tel:0519-81884271 Fax:0519-85788271